




## 60MM PAVERS

# COPING™

Coping™ unit provides a smooth, soft roll to the edge of your patio or step application. Coping can be used for applications such as swimming pools, step treads, deck overhangs, and wall caps.



6x12

### DIMENSIONS

Product	Width (in)	Length (in)	Height (in)	Thickness (mm)	BAND				CUBE				
					Pieces/Sq. Ft.	Bands/Pallet	Sq. Ft./Band	Weight/Band (lbs.)	Pieces/Band	Layers/Pallet	Sq. Ft./Pallet	Pieces/Pallet	Pallet Wgt. (lbs.)
6x12	6	12	2 3/8	60	2	4	26	670	52	4	104	208	2,375

Note: All dimensions shown are nominal.

Color swatches are for reference. Please refer to actual samples for proper color matching.

### PRODUCT DETAILS

- Compressive Strength: The average compressive strength shall not be less than 8000 PSI.
- Resistance to Freeze Thaw Cycle: Dry weight loss not to be greater than 1% of weight when subjected to 50 cycles of freezing and thawing.
- Absorption: The average absorption of test samples shall not be greater than 5%.
- Manufactured in accordance with ASTM C936 specifications.

### STANDARD COLORS



Coastal Tan



Fieldstone



Granite



Mesquite

### ACCENT COLORS



Charcoal



www.newlinehardscapes.com  
New Holland, PA 17557 | 717.354.1200

